

QUICK MOTOR GUIDE



	RATED TORQUE (Nm)	TUBE SIZE (mm)	BLIND WIDTH MIN (mm)	WEIGHT CAPACITY (kg)	NOISE (dBA)	USB-C CHARGING	RATED (rpm)	BATTERY CAPACITY (mAh)	🔌 matter + ⚡HREAD	RATED VOLTAGE (AC)	RATED POWER (Watts)	RATED CURRENT (Amps)	ROLLER	VISION®	ROMASHADE®	PERFECT FIT ROLLER	CELLULAR	VERTICAL	R2180-1CH	R2185-6CH	R2190-16CH	T144-5CH
RECHARGEABLE	MOTOR SPECIFICATIONS												BLIND TYPES				REMOTE CONTROLS					
PERFECT FIT MOTOR DC R2100	0.3	PF	400	1	30	✓	20 30 35	800								•			•	•	•	
500 SERIES DC R2105	0.5	32	460	1.9	30	✓	20 25 30	2600					•	•	•				•	•	•	
1100 SERIES DC R2110	1.1	35/ 40	510	3.5	32	✓	20 25 30	2600					•	•	•				•	•	•	
1100 SERIES DC R2115-SHORT	1.1	35/ 40	355	3.5	32	✓	20 25 30	2500					•	•	•				•	•	•	
2000 SERIES DC R2120	2.0	35 40 45	650	6	32	✓	20 25 30	2500					•	•	•				•	•	•	
2000 SERIES DCM R2125	2.0	35 40 45	650	6	32	✓	20 25 30	2500	✓				•	•	•				•	•	•	
3000 SERIES DC R2130	3.0	40 45	650	8.5	30	✓	20 24 28	5000					•	•	•				•	•	•	
3000 SERIES DCM R2135	3.0	40 45	650	8.5	30	✓	20 24 28	5000	✓				•	•	•				•	•	•	
SLIMLINE VOGUE® DC T140	0.1	-	200			Micro USB	42	2600									•					•
CELLULAR MOTOR DC P4600	0.6	35 40 45	490	3.6		3.5mm Jack	34									•			R1940-1CH R1942-6CH R1944-16CH			
HARD WIRED	MOTOR SPECIFICATIONS												BLIND TYPES				REMOTE CONTROLS					
2000 SERIES AC R2150	2.0	35 40 45	500	5	32		20 24 28			100-240V 50-60HZ	18	0.18	•	•	•				•	•	•	
2000 SERIES ACM R2155	2.0	35 40 45	500	5	32		20 24 28		✓	100-240V 50-60HZ	18	0.18	•	•	•				•	•	•	
6000 SERIES AC R2160	6	55	650	12	32		33			230V 50HZ	146	0.64	•						•	•	•	